



**Combination SCHUKO socket outlet 2gang with frame Berker Q.1, polar white velvety**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	duroplastic
Surface appearance	velvety

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	without spreader claws, for screw fastening
-------------------	---

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Cable**

- 2 x 1gang, wired-through	
----------------------------	--

**Safety**

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

47206089



**Identification**

---

Main design line	Berker Q.1
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---