## product sheet 47428989



47428989



| Technical features                           |                                |
|--|--------------------------------|
| Architecture                                 |                                |
| Design                                       | according to DIN 4944          |
| Fixing mode                                  | flush-mountin                  |
| Connectivity                                 |                                |
| Type of USB port                             | othe                           |
| Main electrical features                     |                                |
| Nominal voltage                              | 250                            |
| Rated voltage                                | 250 V A                        |
| Frequency                                    | 50/60 H                        |
| Rated current                                | 16                             |
| Electric current                             |                                |
| Rated current                                | 16                             |
| Cover, door                                  |                                |
| Cover  | Full cover plat                |
| Materials                                    |                                |
| Colour of design line                        | polar whit                     |
| Colour                                       | polarwhit                      |
| Colour                                       | white                          |
| RAL colour                                   | RAL 9010 - Pure whit           |
| Material                                     | duroplast                      |
| Surface appearance                           | gloss                          |
| Dimensions                                   |                                |
| Insertion depth                              | 32 mr                          |
| Installation depth, flush-mounted boxes      | 31 mr                          |
| Installation, mounting                       |                                |
| Installation mode                            | with spreader claw             |
| Connection                                   |                                |
| Connection terminals                         | according to IEC 60884-        |
| Connection terminals                         | according to VDE 0620-1:2021-0 |
| - with plug-in terminals                     |                                |
| Safety                                       |                                |
| IK protection code against mecanical impacts | C                              |
| Protection index IP                          | IP2                            |



## Identification

Main design line

Berker S.1/B.3/B.7