



47508915



SCHUKO socket outlet with "EDV" imprint Labelling field, Berker S.1/B.3/B.7, red glossy

Technical features

Arc	hite	cti	ire

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "EDV"

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Materials

re	Design lines special colours
re	Colour
rec	Colour
RAL 3003 - Ruby re	RAL colour
duroplast	Material
glos	Surface appearance

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with nlug-in terminals	

Use

Differentiation characteristic 1 - Sales	Labelling field
--	-----------------

Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20

- without enhanced contact protection



Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s) Berker S.1, Berker B	
Instructions	
Information text	Insert colour-coded., Labelling field height arranged for P-touch strips 6 mm.