



47527209



**SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker K.1, polar white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-	with self-closing hinged covers

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with plug-in terminals

**Use**

Differentiation characteristic 1 - Sales	Labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- enhanced contact protection VDE 0620-1:2021-02	

### Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.1

### Instructions

Information text	Labelling field height arranged for 6 mm P-touch strips.
------------------	--

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200). Specially suited to combinations of several socket outlets if right angle plugs are used.