

# Product data sheet

Socket, French/Belgian system, with USB charger



## Reference number

LS 1520 F-15 CA SWM

## Socket, French/Belgian system, with USB charger

2-pole + male earth pin, 16 A / 250 V ~  
 CEE 7/5  
 with enhanced contact protection / shutter (Safety Plus)  
 with 1 USB port type A and 1 USB port type C  
 with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>

Installation in flush box with dimensions according to DIN 49073  
 depth of flush box (inner dimension): min. 57 mm

## Technical data

|                              |                             |
|------------------------------|-----------------------------|
| Rated voltage:               | AC 220 ... 250 V ~          |
| Mains frequency:             | 50/60 Hz                    |
| Rated current, socket:       | 16 A                        |
| Output voltage USB:          | DC 5 V                      |
| Output current USB (total):  | 3 A                         |
| Stand-by power:              | ≤ 25 mW                     |
| Ambient temperature:         | +5 ... +35 °C               |
| Stora/transport temperature: | -20 ... +70 °C              |
| Degree of protection:        | IP 20                       |
| Connection mode:             | screwless terminals         |
| single wire:                 | 1.5 ... 2.5 mm <sup>2</sup> |
| stranded without ferrule:    | 1.5 ... 2.5 mm <sup>2</sup> |

## matt lacquered

**Colour:**  
 matt graphite black

**Material:**  
 thermoplastic lacquered

**P** Colour printing possible