

Product data sheet

Socket, French/Belgian system, with USB charger



Reference number

LS 1520 F-18 C SWM

Socket, French/Belgian system, with USB charger

with 1 USB port type C
with enhanced contact protection / shutter (Safety Plus)
with quick charge function

with screwless terminals for rigid and untreated flexible wires up to 2.5 mm²
Installation in flush box with dimensions according to DIN 49073
2-pole + male earth pin, 16 A / 250 V ~
CEE 7/5
depth of flush box (inner dimension): min. 57 mm

JUNG Quick Charge® supports these standards

Technical data

| | |
|------------------------------|-----------------------------|
| Rated voltage: | AC 220 ... 250 V ~ |
| Mains frequency: | 50/60 Hz |
| Rated current, socket: | 16 A |
| Output voltage USB: | DC 9 V / DC 5 V |
| Output current USB: | 2 A / 3 A |
| Stand-by power: | ≤ 25 mW |
| Ambient temperature: | +5 ... +35 °C |
| Stora/transport temperature: | -20 ... +70 °C |
| Degree of protection: | IP 20 |
| Connection mode: | screwless terminals |
| single wire: | 1.5 ... 2.5 mm ² |
| stranded without ferrule: | 1.5 ... 2.5 mm ² |



Surface finish:
matt lacquered

Colour:
matt graphite black

Material:
thermoplastic lacquered

P Colour printing possible