

Product data sheet

Socket, French/Belgian system, with USB charger



Reference number

LS 1520 F-18 C WWM

Socket, French/Belgian system, with USB charger

with 1 USB port type C
with enhanced contact protection / shutter (Safety Plus)
with quick charge function

with screwless terminals for rigid and untreated flexible wires up to 2.5 mm²
Installation in flush box with dimensions according to DIN 49073
2-pole + male earth pin, 16 A / 250 V ~
CEE 7/5
depth of flush box (inner dimension): min. 57 mm

JUNG Quick Charge® supports these standards

Technical data

Rated voltage:	AC 220 ... 250 V ~
Mains frequency:	50/60 Hz
Rated current, socket:	16 A
Output voltage USB:	DC 9 V / DC 5 V
Output current USB:	2 A / 3 A
Stand-by power:	≤ 25 mW
Ambient temperature:	+5 ... +35 °C
Stora/transport temperature:	-20 ... +70 °C
Degree of protection:	IP 20
Connection mode:	screwless terminals
single wire:	1.5 ... 2.5 mm ²
stranded without ferrule:	1.5 ... 2.5 mm ²



Surface finish:
matt lacquered

Colour:
matt snow white

Material:
thermoplastic lacquered

P Colour printing possible