

# Product data sheet

Socket, French/Belgian system, with USB charger



## Reference number

LS 1520 F-18 C

## Socket, French/Belgian system, with USB charger

2-pole + male earth pin, 16 A / 250 V ~  
 CEE 7/5  
 with enhanced contact protection / shutter (Safety Plus)  
 with 1 USB port type C  
 with quick charge function  
 with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>

Installation in flush box with dimensions according to DIN 49073  
 depth of flush box (inner dimension): min. 57 mm

JUNG Quick Charge® supports these standards

## Technical data

Rated voltage:	AC 220 ... 250 V ~
Mains frequency:	50/60 Hz
Rated current, socket:	16 A
Output voltage USB:	DC 9 V / DC 5 V
Output current USB:	2 A / 3 A
Stand-by power:	≤ 25 mW
Ambient temperature:	+5 ... +35 °C
Stora/transport temperature:	-20 ... +70 °C
Degree of protection:	IP 20
Connection mode:	screwless terminals
single wire:	1.5 ... 2.5 mm <sup>2</sup>
stranded without ferrule:	1.5 ... 2.5 mm <sup>2</sup>



Thermoplastic (breakproof) high-gloss

Colour:  
 ivory

Material:  
 thermoplastic

**P** Colour printing possible