

Product data sheet

HDMI / VGA



Reference number

MA LS 1173

HDMI / VGA

with supporting frame, screw fixing only

Consider bending radius and various plug types. Ensure sufficient installation space.

Spare part:

adapter 3 ref.-no.: MA 1000 AD 3

Technical data

Technical data HDMI

| | |
|----------------------|---|
| Standard: | HDMI 2.0a |
| Video formats: | 4K @ 50/60 Hz, Full HD @ 48 Hz 3D, HDR Video |
| Terminal: | HDMI™ type A, 180° |
| Contact material: | gold-plated |
| Installation depth: | 25 mm |
| Ambient temperature: | -5 ... +45 °C |
| Installation note: | Consider bending radius and various plug types. Ensure sufficient installation space. |

Technical data VGA

| | |
|---------------------------|--|
| Resolution: | ≥ 800 x 600 pixels ≤ 1280 x 1024 pixels S-VGA compatible |
| Frequency range: | ≤ 160 MHz |
| Contact resistance: | ≤ 30 mΩ |
| Insulation resistance: | ≥ 1,000 MΩ |
| Electric strength: | AC 500 V ~ (50/60 Hz) at 1 min 2 mA |
| Insertion forces: | 43.9 N |
| Removal forces: | 3.92 N |
| Insertion/removal cycles: | ≥ 500 |
| Terminal: | 15-pole D-sub, 180° |
| Installation depth: | 5 mm |
| Ambient temperature: | -5 ... +45 °C |
| Installation note: | Installation into deep wall box |

Thermoplastic (breakproof) high-gloss

Colour:
ivory

Material:
thermoplastic

P Colour printing possible