



10122174



Frame 2gang Berker R.1, Aluminium/polar white

Technical features

Architecture

| | |
|-------------------|-------|
| Technical version | 2gang |
|-------------------|-------|

Capacity

| | |
|-------------------|---|
| Number of sockets | 2 |
|-------------------|---|

Materials

| | |
|---------------------------|----------------------------|
| Colour of design line | Aluminium/polar white |
| Colour | aluminium |
| Colour | aluminium optics |
| RAL colour | RAL 9006 - White aluminium |
| Material / workmanship | aluminium, anodised |
| Material | Aluminium |
| Surface appearance | matt/glossy |
| Type of surface treatment | untreated |

Dimensions

| | |
|--------|----------|
| Depth | 9,9 mm |
| Height | 81,2 mm |
| Width | 152,2 mm |

Installation, mounting

| | |
|-------------------|---|
| Installation mode | for vertical and horizontal mounting, clamp fastening |
|-------------------|---|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Identification

| | |
|------------------|------------|
| Main design line | Berker R.1 |
|------------------|------------|

Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.