



16286084



## Rocker with labelling field, Lens, Berker Q.1/Q.3/Q.7/Q.9

### Technical features

### Controls and indicators

- also for KNX applications: push-button, 1 gang, and group push-button, 1 gang
- for rocker push-buttons
- for change-over/intermediate switch

### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety

### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

### Equipment

- for lighting and monitoring circuit

### Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	Lens

### Identification

Application, usage	Flush-mounted wet-room installation, Light control, KNX - operating systems
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

### Instructions

Information text	For labelling with names, notes etc.
------------------	--------------------------------------

- The IP44 degree of protection can only be achieved in conjunction with the appropriate room, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons. Labelling field height designed for 6 mm P-touch strip.