



3315418989



**VGA socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, polar white glossy**

Technical features

**Architecture**

Technical version with screw-in lift terminals

**Connectivity**

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

**Frequency**

Frequency range video max. 160 MHz

**Screen**

Resolution max. 1280 x 1024 px

**Materials**

Colour of design line polar white

Colour polarwhite

RAL colour RAL 9010 - Pure white

Material Plastic/metal

Surface appearance glossy

**Installation, mounting**

Installation mode without spreader claws, for screw fastening

**Connection**

Conductor cross-section max. 1,5 mm<sup>2</sup>

- with screw-in lift terminals for connection to 15-core VGA cable

**Equipment**

- with supporting ring

**Use**

Differentiation characteristic 3 - Sales with screw-in lift terminals

**Identification**

Application, usage Communication technology

Main design line Berker S.1/B.3/B.7

Secondary design line(s) Berker S.1, Berker B.3, Berker B.7

### Instructions

---

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74

---