



47228989

SCHUKO socket outlet with cover plate with enhanced touch protection, Berker S.1/B.3/B.7, polar white glossy

Technical features

Arc	hitect	ıırα
AIL	HILECL	uic

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
nateu current	IUA

Cover, door

Cover	Full cover plate
-------	------------------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	duroplastic
Surface appearance	glossy

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

to an Handan are also	and the second and a second
Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker S.1/B.3/B.7