



47403533



IP55

SCHUKO socket outlet w. green hing. cov. and symbol Berker W.1, grey/light grey matt

Technical features

Architecture

Design according to DIN 49440

Fixing mode surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

Type of USB port other

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

Electric current

Rated current 16 A

Cover, door

Cover Complete housing

- with hinged cover that falls back, manual clip-in

Materials

Colour of design line grey/light grey

Colour light grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

Installation, mounting

Installation mode for screw fastening

Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

IK protection code against mechanical impacts 05

Protection index IP IP55

- without enhanced contact protection

Use conditions

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

Identification

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

Instructions

Information text Hinged cover springs made of stainless steel, pins
of quick-release lock made of ZAMAK
