



50463525



Push-button insert, change-over contact, illuminated surface-mounted/flush-mounted with lens, Berker W.1, grey matt

Technical features

Architecture

Type of control unit rocker

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Electric current

Momentary-contact current 10 A

Materials

Colour of design line grey

Colour iron grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

Dimensions

Depth 42 mm

Height 71 mm

Width 71 mm

Installation, mounting

Installation mode for screw fastening

Connection

- with plug-in terminals
- with N-terminal

Equipment

- with blue 230 V LED unit
- for lighting and monitoring circuit

Use

Differentiation characteristic 2 - Sales with lens

Safety

Protection index IP IP55

Use conditions

Operating temperature -40...30 °C

Identification

| | |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line | Berker W.1 |

Instructions

| | |
|------------------|--|
| Information text | Pins of quick-release lock made of ZAMAK |
|------------------|--|

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
