



6765102089





Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals, Serie R.classic, polar white glossy

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Power

Power consumption	0.25 W/0.35 VA

Cover, door

Cover	Central cover plate

Detection

 integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

polarwhite
black
RAL 9010 - Pure white
thermoplastic
glossy
_

Lighting control

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0.2 cd

LED control

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Conductor cross-section (rigid)	max. 2,5 mm²
Connection terminals	according to IEC 60884-1

- with screw-in lift terminals



Cable

- through-wiring possible, therefore also ideal for retrofitting

Equipment

- additional benefit by combination of a socket outlet with an orientation light

Use

Differentiation characteristic 2 - Sales enhanced contact protection

Differentiation characteristic 3 - Sales Screw-in lift terminals

Safety

Enhanced contact protection according to IEC 60884-1

- Enhanced contact protection

Identification

Main design line Serie R.classic

Instructions

Information text

Caution!

Items with special flush-mounted insert.

Centre plates with LED orientation lights are not compatible with the standard socket outlets.